

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2  
Revision date: 23/01/2019

Page 1 of 18  
Print date: 23/01/2019

### SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: Barniz B930 CRYSTAL DRY - FINTECH  
Product Code: B930

#### 1.2 Relevant identified uses of the mixture and uses advised against.

Finishing at color protection

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **Custom Creative SL**  
Address: c/Sevilla 43  
City: Jerez de La Frontera  
Province: Cádiz  
Telephone: +34 956 045 939  
E-mail: info@fintechrefinish.com  
Web: www.fintechrefinish.com

**1.4 Emergency telephone number:** +34 956 045 939 (Only available during office hours; Monday-Friday; 08:00-18:00)

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.

Flam. Liq. 3 : Flammable liquid and vapour.

Skin Sens. 1 : May cause an allergic skin reaction.

#### 2.2 Label elements.

##### **Labelling in accordance with Regulation (EU) No 1272/2008:**

##### Pictograms:



Signal Word:

#### **Warning**

H statements:

H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

P statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P370+P378	In case of fire: Use... to extinguish.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2

Revision date: 23/01/2019

Page 2 of 18

Print date: 23/01/2019

P501 Dispose of contents/container to ...

### EUH statements:

- EUH208 Contains A mixture of:  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene);  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxy poly(oxyethylene). May produce an allergic reaction.
- EUH208 Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate. May produce an allergic reaction.
- EUH208 Contains methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

Contains:  
tetraethyl N,N'-(methylenedicyclohexane-4,1-diyl)bis--aspartate

### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not Applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 607-521-00-8 CAS No: 136210-30-5 EC No: 429-270-1 Registration No: 01-0000017556-64-XXXX	tetraethyl N,N'-(methylenedicyclohexane-4,1-diyl)bis--aspartate	25 - 75 %	Aquatic Chronic 3, H412 - Skin Sens. 1, H317	-
Index No: 607-025-00-1 CAS No: 123-86-4 EC No: 204-658-1 Registration No: 01-2119485493-29-XXXX	[1] n-butyl acetate	10 - 20 %	Flam. Liq. 3, H226 - STOT SE 3, H336	-
Index No: 606-026-00-4 CAS No: 110-12-3 EC No: 203-737-8 Registration No: 01-2119472300-51-XXXX	[1] 5-methylhexan-2-one, isoamyl methyl ketone	1 - 10 %	Acute Tox. 4 *, H332 - Flam. Liq. 3, H226	-
Index No: 607-195-00-7 CAS No: 108-65-6 EC No: 203-603-9 Registration No: 01-2119475791-29-XXXX	[1] 2-methoxy-1-methylethyl acetate	2.5 - 10 %	Flam. Liq. 3, H226	-
EC No: 918-668-5 Registration No: 01-2119455851-35-XXXX	Hydrocarbons, C9, aromatics	2.5 - 10 %	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - STOT SE 3, H335 - STOT SE 3, H336	-

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2

Revision date: 23/01/2019

Page 3 of 18

Print date: 23/01/2019

CAS No: 623-91-6 EC No: 210-819-7	Diethyl fumarate	1 - 2.5 %	Acute Tox. 4, H302	-
Index No: 601-022-00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01-2119488216-32-XXXX	[1] xylene (Mixture of isomers)	1 - 10 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
Index No: 607-038-00-2 CAS No: 112-07-2 EC No: 203-933-3 Registration No: 01-2119475112-47-XXXX	[1] 2-butoxyethyl acetate, butylglycol acetate	1 - 2.5 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332	-
CAS No: 104810-47-1 EC No: 400-830-7 Registration No: 01-0000015075-76-XXXX	A mixture of: $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene), $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionylpoly(oxyethylene)	0.1 - 1 %	Aquatic Chronic 2, H411 - Skin Sens. 1, H317	-
CAS No: 41556-26-7 EC No: 255-437-1	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	0.1 - 0.25 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Skin Sens. 1, H317	-
CAS No: 82919-37-7 EC No: 280-060-4	methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	0.1 - 0.25 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Skin Sens. 1, H317	-
Index No: 601-023-00-4 CAS No: 100-41-4 EC No: 202-849-4 Registration No: 01-2119489370-35-XXXX	[1] ethylbenzene	0 - 10 %	Acute Tox. 4 *, H332 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - STOT RE 2, H373(órganos de audición)	-
Index No: 601-021-00-3 CAS No: 108-88-3 EC No: 203-625-9 Registration No: 01-2119471310-51-XXXX	[1] toluene	0 - 3 %	Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - Repr. 2, H361d *** - STOT RE 2 *, H373 ** - STOT SE 3, H336 - Skin Irrit. 2, H315	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

\*, \*\*, \*\*\* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

### SECTION 4: FIRST AID MEASURES.

#### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2

Revision date: 23/01/2019

Page 4 of 18

Print date: 23/01/2019

### **Inhalation.**

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

### **Eye contact.**

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

### **Skin contact.**

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

### **Ingestion.**

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

### **4.2 Most important symptoms and effects, both acute and delayed.**

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

### **4.3 Indication of any immediate medical attention and special treatment needed.**

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. If the person vomits, clear the respiratory tract. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

## **SECTION 5: FIREFIGHTING MEASURES.**

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

### **5.1 Extinguishing media.**

#### **Suitable extinguishing media:**

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

#### **Unsuitable extinguishing media:**

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

### **5.2 Special hazards arising from the mixture.**

#### **Special risks.**

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

### **5.3 Advice for firefighters.**

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

### **Fire protection equipment.**

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

### **6.1 Personal precautions, protective equipment and emergency procedures.**

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2

Revision date: 23/01/2019

Page 5 of 18

Print date: 23/01/2019

### 6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

### 6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

## SECTION 7: HANDLING AND STORAGE.

### 7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

### 7.3 Specific end use(s).

Not available.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
n-butyl acetate	123-86-4	United Kingdom [1]	<b>Eight hours</b>	150	724
			<b>Short term</b>	200	966
		United States [2] (Cal/OSHA)	<b>Eight hours</b>	150	
			<b>Short term</b>	200	
		United States [3] (NIOSH)	<b>Eight hours</b>	150	
			<b>Short term</b>	200	
United States [4] (OSHA)		<b>Eight hours</b>	150	710	
		<b>Short term</b>			
5-methylhexan-2-one, isoamyl methyl ketone	110-12-3	European Union [5]	<b>Eight hours</b>	20	95
			<b>Short term</b>		

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## B930-Barniz B930 CRYSTAL DRY - FINTECH

Version: 2

Revision date: 23/01/2019

Page 6 of 18

Print date: 23/01/2019

		United Kingdom [1]	<b>Eight hours</b>	20	95
			<b>Short term</b>	100	475
		United States [2] (Cal/OSHA)	<b>Eight hours</b>	50	
			<b>Short term</b>		
		United States [3] (NIOSH)	<b>Eight hours</b>	50	
			<b>Short term</b>		
2-methoxy-1-methylethyl acetate	108-65-6	European Union [5]	<b>Eight hours</b>	50 (skin)	275 (skin)
			<b>Short term</b>	100 (skin)	550 (skin)
xylene (Mixture of isomers)	1330-20-7	United Kingdom [1]	<b>Eight hours</b>	50	274
			<b>Short term</b>	100	548
		European Union [5]	<b>Eight hours</b>	50 (skin)	221 (skin)
			<b>Short term</b>	100 (skin)	442 (skin)
		United States [2] (Cal/OSHA)	<b>Eight hours</b>	100	
			<b>Short term</b>	150 (Ceiling) 300	
2-butoxyethyl acetate, butylglycol acetate	112-07-2	United States [3] (NIOSH)	<b>Eight hours</b>	100	
			<b>Short term</b>	150	
ethylbenzene	100-41-4	United States [4] (OSHA)	<b>Eight hours</b>	100	435
			<b>Short term</b>		
		European Union [5]	<b>Eight hours</b>	20 (skin)	133 (skin)
			<b>Short term</b>	50 (skin)	333 (skin)
		United Kingdom [1]	<b>Eight hours</b>	20	133
			<b>Short term</b>	50	332
toluene	108-88-3	United States [2] (Cal/OSHA)	<b>Eight hours</b>	100 (skin)	442 (skin)
			<b>Short term</b>	200 (skin)	884 (skin)
		United States [3] (NIOSH)	<b>Eight hours</b>	100	441
			<b>Short term</b>	125	552
		United States [4] (OSHA)	<b>Eight hours</b>	5	
			<b>Short term</b>	30	
		European Union [5]	<b>Eight hours</b>	100	
			<b>Short term</b>	100	
		United States [2] (Cal/OSHA)	<b>Eight hours</b>	100	
			<b>Short term</b>	125	
		United States [3] (NIOSH)	<b>Eight hours</b>	100	435
			<b>Short term</b>		
		European Union [5]	<b>Eight hours</b>	50 (skin)	192 (skin)
			<b>Short term</b>	100 (skin)	384 (skin)
		United Kingdom [1]	<b>Eight hours</b>	50	191
			<b>Short term</b>	100	384
		United States [2] (Cal/OSHA)	<b>Eight hours</b>	10	
			<b>Short term</b>	150 (Ceiling) 500	
		United States [3] (NIOSH)	<b>Eight hours</b>	100	
			<b>Short term</b>	150	
		United States [4] (OSHA)	<b>Eight hours</b>	200	
			<b>Short term</b>	300 Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift: 500 [10 min]	

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[2] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[3] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2

Revision date: 23/01/2019

Page 7 of 18

Print date: 23/01/2019

[4] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[5] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
tetraethyl N,N'-(methylenedicyclohexane-4,1-diyl)bis--aspartate CAS No: 136210-30-5 EC No: 429-270-1	DNEL (Workers)	Inhalation, Long-term, Systemic effects	84 (mg/m <sup>3</sup> )
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	DNEL (Workers)	Inhalation, Long-term, Systemic effects	480 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	102,34 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Systemic effects	960 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Systemic effects	859,7 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Long-term, Local effects	480 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Local effects	102,34 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Local effects	960 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Local effects	859,7 (mg/m <sup>3</sup> )
	DNEL (General population)	Oral, Long-term, Systemic effects	3,4 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	3,4 (mg/kg bw/day)
5-methylhexan-2-one, isoamyl methyl ketone CAS No: 110-12-3 EC No: 203-737-8	DNEL (Workers)	Inhalation, Long-term, Systemic effects	95 (mg/m <sup>3</sup> )
2-methoxy-1-methylethyl acetate CAS No: 108-65-6 EC No: 203-603-9	DNEL (Workers)	Inhalation, Long-term, Systemic effects	275 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	33 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	153,5 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	54,8 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	1,67 (mg/kg bw/day)
Hydrocarbons, C9, aromatics CAS No: EC No: 918-668-5	DNEL (Workers)	Inhalation, Long-term, Systemic effects	150 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	32 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	25 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	11 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	11 (mg/kg bw/day)
xylene (Mixture of isomers) CAS No: 1330-20-7 EC No: 215-535-7	DNEL (Workers)	Inhalation, Long-term, Systemic effects	77 (mg/m <sup>3</sup> )

-Continued on next page.-



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2

Revision date: 23/01/2019

Page 8 of 18

Print date: 23/01/2019

2-butoxyethyl acetate, butylglycol acetate CAS No: 112-07-2 EC No: 203-933-3	DNEL (Workers)	Inhalation, Long-term, Systemic effects	133 (mg/m <sup>3</sup> )
ethylbenzene CAS No: 100-41-4 EC No: 202-849-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	77 (mg/m <sup>3</sup> )
toluene CAS No: 108-88-3 EC No: 203-625-9	DNEL (Workers)	Inhalation, Long-term, Local effects	192 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Local effects	56,5 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	192 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	56,5 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Systemic effects	384 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Systemic effects	226 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Local effects	384 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Local effects	226 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	384 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	226 (mg/kg bw/day)
DNEL (General population)	Oral, Long-term, Systemic effects	8,13 (mg/kg bw/day)	

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	aqua (freshwater)	0,18 (mg/l)
	aqua (marine water)	0,018 (mg/l)
	aqua (intermittent releases)	0,36 (mg/l)
	PNEC STP	35,6 (mg/l)
	sediment (freshwater)	0,981 (mg/kg sediment dw)
	sediment (marine water)	0,0981 (mg/kg sediment dw)
	2-methoxy-1-methylethyl acetate CAS No: 108-65-6 EC No: 203-603-9	aqua (freshwater)
aqua (marine water)		0,0635 (mg/L)
aqua (intermittent releases)		6,35 (mg/L)
PNEC STP		100 (mg/L)
sediment (freshwater)		3,29 (mg/kg sediment dw)
sediment (marine water)		0,329 (mg/kg sediment dw)
soil		0,29 (mg/kg soil dw)
toluene CAS No: 108-88-3 EC No: 203-625-9	aqua (freshwater)	0,68 (mg/L)
	aqua (marine water)	0,68 (mg/L)
	aqua (intermittent releases)	0,68 (mg/L)

-Continued on next page.-



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2

Revision date: 23/01/2019

Page 9 of 18

Print date: 23/01/2019




	PNEC STP	13,61 (mg/L)
	sediment (freshwater)	16,39 (mg/kg sediment dw)
	sediment (marine water)	16,39 (mg/kg sediment dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

<b>Concentration:</b>	<b>100 %</b>		
<b>Uses:</b>	<b>Finishing at color protection</b>		
<b>Breathing protection:</b>	If the recommended technical measures are observed, no individual protection equipment is necessary.		
<b>Hand protection:</b>	PPE: Work gloves. Characteristics: «CE» marking, category I. CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420 Maintenance: Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Observations: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
<b>Material:</b>	PVC (polyvinyl chloride)	Breakthrough time (min.): > 480	Material thickness (mm): 0,35
<b>Eye protection:</b>	PPE: Face shield. Characteristics: «CE» marking, category II. Face and eye protector against splashing liquid. CEN standards: EN 165, EN 166, EN 167, EN 168 Maintenance: Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Observations: Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.		
<b>Skin protection:</b>	PPE: Anti-static protective clothing. Characteristics: «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. CEN standards: EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5 Maintenance: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. Observations: The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.		
	PPE: Anti-static safety footwear. Characteristics: «CE» marking, category II. CEN standards: EN ISO 13287, EN ISO 20344, EN ISO 20346 Maintenance: The footwear should be checked regularly Observations: The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.		

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2

Revision date: 23/01/2019

Page 10 of 18

Print date: 23/01/2019

### 9.1 Information on basic physical and chemical properties.

Appearance: Transparent liquid with characteristic odour

Colour: N.A./N.A.

Odour: N.A./N.A.

Odour threshold: N.A./N.A.

pH: N.A./N.A.

Melting point: N.A./N.A.

Boiling Point: 128 °C

Flash point: 46 °C

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

Lower Explosive Limit: N.A./N.A.

Upper Explosive Limit: N.A./N.A.

Vapour pressure: 10,411

Vapour density: N.A./N.A.

Relative density: 1,012

Solubility: N.A./N.A.

Liposolubility: N.A./N.A.

Hydrosolubility: N.A./N.A.

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A.

Oxidizing properties: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

### 9.2 Other information.

Dropping point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

## SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

If the storage conditions are satisfied, does not produce dangerous reactions.

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

### 10.4 Conditions to avoid.

Avoid the following conditions:

- High temperature.
- Static discharge.
- Contact with incompatible materials.
- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

### 10.5 Incompatible materials.

Avoid the following materials:

- Explosives materials.
- Toxic materials.
- Oxidizing materials.

### 10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2

Revision date: 23/01/2019

Page 11 of 18

Print date: 23/01/2019

### SECTION 11: TOXICOLOGICAL INFORMATION.

2-butoxyethanol and its acetate are easily absorbed by the skin and can cause noxious effects to the kidneys.

#### 11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

#### Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
n-butyl acetate  CAS No: 123-86-4      EC No: 204-658-1	Oral	LD50	Rat	10800 mg/kg bw [1] [1] Acute Toxicity Data. Journal of the American College of Toxicology, Part B. Vol. 1, Pg. 196, 1992
	Dermal	LD50	Rabbit	>17600 mg/kg bw [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 7, 1974
	Inhalation	LC50	Rat	1.85 mg/l/4 h [1] [1] Inhalation Toxicology. Vol. 9, Pg. 623, 1997
2-methoxy-1-methylethyl acetate  CAS No: 108-65-6      EC No: 203-603-9	Oral	LD50	Rat	6190 mg/kg bw [1] [1] Study report, 1985. OECD Guideline 401 (Acute Oral Toxicity).
	Dermal	LD50	Rabbit	>5000 mg/kg bw [1] [1] Dow Chemical Company Reports. Vol. MSD-1582
	Inhalation	LC0	Rat	>4345 ppm (6 h) [1] [1] Study report, 1980. OECD Guideline 403 (Acute Inhalation Toxicity).
Hydrocarbons, C9, aromatics  CAS No:                      EC No: 918-668-5	Oral	LD50	Rat	6900 mg/kg/bw
	Dermal			
	Inhalation			
xylene (Mixture of isomers)  CAS No: 1330-20-7      EC No: 215-535-7	Oral	LD50	Rat	4300 mg/kg bw [1] [1] AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956
	Dermal	LD50	Rabbit	> 1700 mg/kg bw [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974
	Inhalation	LC50	Rat	21,7 mg/l/4 h [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974
ethylbenzene	Oral	LD50	Rat	3500 mg/kg bw [1] [1] AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956
	Dermal	LD50	Rabbit	15400 mg/kg bw [1] [1] Food and Cosmetics Toxicology. Vol. 13, Pg. 803, 1975

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2

Revision date: 23/01/2019

Page 12 of 18

Print date: 23/01/2019

CAS No: 100-41-4	EC No: 202-849-4	Inhalation	
------------------	------------------	------------	--

a) acute toxicity;

Not conclusive data for classification.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 34.921 mg/kg

ATE (Oral) = 22.989 mg/kg

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;

Not conclusive data for classification.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitizer, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Based on available data, the classification criteria are not met.

h) STOT-single exposure;

Based on available data, the classification criteria are not met.

i) STOT-repeated exposure;

Based on available data, the classification criteria are not met.

j) aspiration hazard;

Based on available data, the classification criteria are not met.

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
n-butyl acetate	Fish	LC50	Fish	81 mg/l (96 h) [1]
				[1] Wellens, H. 1982. Comparison of the Sensitivity of Brachydanio rerio and Leuciscus idus by Testing the Fish Toxicity of Chemicals and Wastewaters. Z.Wasser-Abwasser-Forsch. 51(2):49-52 (GER) (ENG ABS). Dawson, G.W., A.L. Jennings, D. Drozdowski, and E. Rider 1977. The Acute Toxicity of 47 Industrial Chemicals to Fresh and Saltwater Fishes. J.Hazard.Mater. 1(4):303-318 (OECDG Data File)
	Aquatic invertebrates	EC50	Daphnia sp.	44 mg/l (48 h) [1]
				[1] publication, 1959

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2

Revision date: 23/01/2019

Page 13 of 18

Print date: 23/01/2019

CAS No: 123-86-4      EC No: 204-658-1	Aquatic plants	Desmodemus subspicatus (reported as Scenedesmus subspicatus) EC50      as      674.7 mg/l (72 h) [1] [1] Method: other: algae growth inhibition test, according to Umweltbundesamt (German Federal Environment Agency) (proposal/draft, version February 1984)
	Fish	LC50      Oryzias latipes      100 mg/L (96 h) [1] [1] Environment Agency of Japan (1998)
2-methoxy-1-methylethyl acetate  CAS No: 108-65-6      EC No: 203-603-9	Aquatic invertebrates	EC50      Daphnia magna      407 mg/L (48 h) [1] [1] Environment Agency of Japan (1998)
	Aquatic plants	EC50      Selenastrum capricornutum (Pseudokirchnerella subcapitata)      >1000 mg/L (72 h) [1] [1] Environment Agency of Japan (1998)
Hydrocarbons, C9, aromatics  CAS No:      EC No: 918-668-5	Fish	LC50      fish      9.22 mg/L (24 h)
	Aquatic invertebrates	
	Aquatic plants	
xylene (Mixture of isomers)  CAS No: 1330-20-7      EC No: 215-535-7	Fish	LC50      Fish      15,7 mg/l (96 h) [1] [1] Bailey, H.C., D.H.W. Liu, and H.A. Javitz 1985. Time/Toxicity Relationships in Short-Term Static, Dynamic, and Plug-Flow Bioassays. In: R.C.Bahner and D.J.Hansen (Eds.), Aquatic Toxicology and Hazard Assessment, 8th Symposium, ASTM STP 891, Philadelphia, PA :193-212
	Aquatic invertebrates	LC50      Crustacean      8,5 mg/l (48 h) [1] [1] Tatem, H.E., B.A. Cox, and J.W. Anderson 1978. The Toxicity of Oils and Petroleum Hydrocarbons to Estuarine Crustaceans. Estuar.Coast.Mar.Sci. 6(4):365-373. Tatem, H.E. 1975. The Toxicity and Physiological Effects of Oil and Petroleum Hydrocarbons on Estuarine Grass Shrimp Palaemonetes pugio (Holthuis). Ph.D.Thesis, Texas A&M University, College Station, TX :133 p
	Aquatic plants	
ethylbenzene	Fish	LC50      Fish      80 mg/l (96 h) [1] [1] Mayer, F.L.Jr., and M.R. Ellersieck 1986. Manual of Acute Toxicity: Interpretation and Data Base for 410 Chemicals and 66 Species of Freshwater Animals. Resour.Publ.No.160, U.S.Dep.Interior, Fish Wildl.Serv., Washington, DC :505 p. (USGS Data File)
	Aquatic invertebrates	LC50      Crustacean      16,2 mg/l (48 h) [1] [1] MacLean, M.M., and K.G. Doe 1989. The Comparative Toxicity of Crude and Refined Oils to Daphnia magna and Artemia. Environment Canada, EE-111, Dartmouth, Nova Scotia :64 p
	Aquatic plants	EC50      Algae      5 mg/l (72 h) [1]

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2

Revision date: 23/01/2019

Page 14 of 18

Print date: 23/01/2019

CAS No: 100-41-4	EC No: 202-849-4		[1] Galassi, S., M. Mingazzini, L. Vigano, D. Cesareo, and M.L. Tosato 1988. Approaches to Modeling Toxic Responses of Aquatic Organisms to Aromatic Hydrocarbons. Ecotoxicol.Environ.Saf. 16(2):158-169. Masten, L.W., R.L. Boeri, and J.D. Walker 1994. Strategies Employed to Determine the Acute Aquatic Toxicity of Ethyl Benzene, a Highly Volatile, Poorly Water-Soluble Chemical. Ecotoxicol.Environ.Saf. 27(3):335-348
toluene		Fish	LC50 Fish 31,7 mg/l (96 h) [1] [1] Geiger, D.L., L.T. Brooke, and D.J. Call 1990. Acute Toxicities of Organic Chemicals to Fathead Minnows (Pimephales promelas), Volume 5. Ctr.for Lake Superior Environ.Stud., Univ.of Wisconsin-Superior, Superior, WI :332 p
		Aquatic invertebrates	LC50 Crustacean 92 mg/l (48 h) [1] [1] MacLean, M.M., and K.G. Doe 1989. The Comparative Toxicity of Crude and Refined Oils to Daphnia magna and Artemia. Environment Canada, EE-111, Dartmouth, Nova Scotia :64 p
		Aquatic plants	EC50 Algae 12,5 mg/l (72 h) [1] [1] Galassi, S., M. Mingazzini, L. Vigano, D. Cesareo, and M.L.Tosato 1988. Approaches to Modeling Toxic Responses of Aquatic Organisms to Aromatic Hydrocarbons. Ecotoxicol.Environ.Saf. 16(2):158-169
CAS No: 108-88-3	EC No: 203-625-9		

### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	1,78	-	-	Very low
5-methylhexan-2-one,isoamyl methyl ketone CAS No: 110-12-3 EC No: 203-737-8	1,88	-	-	Very low
ethylbenzene CAS No: 100-41-4 EC No: 202-849-4	3,15	-	-	Moderate
toluene CAS No: 108-88-3 EC No: 203-625-9	2,73	-	-	Low

### 12.4 Mobility in soil.

No information is available about the mobility in soil.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



**Version: 2**  
**Revision date: 23/01/2019**

**Page 15 of 18**  
**Print date: 23/01/2019**

The product must not be allowed to go into sewers or waterways.  
Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

## SECTION 13 DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

## SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

### 14.1 UN number.

UN No: UN1263

### 14.2 UN proper shipping name.

Description:

ADR: UN 1263, PAINT, 3, PG III, (D/E)

IMDG: UN 1263, PAINT, 3, PG III

ICAO/IATA: UN 1263, PAINT, 3, PG III

### 14.3 Transport hazard class(es).

Class(es): 3

### 14.4 Packing group.

Packing group: III

### 14.5 Environmental hazards.

Marine pollutant: No

### 14.6 Special precautions for user.

Labels: 3



Hazard number: 30

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 10 L

-Continued on next page.-



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2

Revision date: 23/01/2019

Page 16 of 18

Print date: 23/01/2019

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.  
Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E  
Proceed in accordance with point 6.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

## SECTION 15: REGULATORY INFORMATION.

### 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

#### Volatil organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): D - Topcoat (All types)

Phase I\* (from 01/01/2007): 420 g/l

Phase II\* (from 01/01/2010): 420 g/l

(\* ) g/l ready to use

VOC content (p/p): 25,465 %

VOC content: 257,639 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
48. Toluene CAS No 108-88-3 EC No 203-625-9	Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Kind of pollutant for the water (Germany): WGK 2: Hazardous for the water. (Autoclassified according to the AwSV Regulations)

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



Version: 2

Revision date: 23/01/2019

Page 17 of 18

Print date: 23/01/2019

H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.(órganos de audición)
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4  
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4  
Acute Tox. 4 : Acute toxicity (Oral), Category 4  
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1  
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1  
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2  
Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3  
Asp. Tox. 1 : Aspiration toxicity, Category 1  
Flam. Liq. 2 : Flammable liquid, Category 2  
Flam. Liq. 3 : Flammable liquid, Category 3  
Repr. 2 : Reproductive toxicant, Category 2  
STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2  
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3  
Skin Irrit. 2 : Skin irritant, Category 2  
Skin Sens. 1 : Skin sensitiser, Category 1

Sections changed compared with the previous version:

1,2,3,4,8,9,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
AwSV: Facility Regulations for handling substances that are hazardous for the water.  
BCF: Bioconcentration factor.  
CEN: European Committee for Standardization.  
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.  
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.  
EC50: Half maximal effective concentration.  
PPE: Personal protection equipment.  
IATA: International Air Transport Association.  
ICAO: International Civil Aviation Organization.  
IMDG: International Maritime Code for Dangerous Goods.  
LC50: Lethal concentration, 50%.  
LD50: Lethal dose, 50%.  
Log Pow: Logarithm of the partition octanol-water.  
NOEC: No observed effect concentration.  
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.  
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.  
WGK: Water hazard classes.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>  
<http://echa.europa.eu/>

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## B930-Barniz B930 CRYSTAL DRY - FINTECH



**Version: 2**

**Revision date: 23/01/2019**

**Page 18 of 18**

**Print date: 23/01/2019**

Regulation (EU) 2015/830.  
Regulation (EC) No 1907/2006.  
Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.