

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ST-55-DISOLVENTE ST-55 RAPIDO FINTECH



Version: 1  
Revision date: 29/11/2018

Page 1 of 13  
Print date: 29/11/2018

### SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: DISOLVENTE ST-55 RAPIDO FINTECH  
Product Code: ST-55

#### 1.2 Relevant identified uses of the mixture and uses advised against.

Dilution and cleaning of solvent base products Custom Creative

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **Custom Creative SL**  
Address: c/Sevilla 43  
City: Jerez de La Frontera  
Province: Cádiz  
Telephone: +34 956 045 939  
E-mail: info@fintechrefinish.com  
Web: www.fintechrefinish.com

**1.4 Emergency telephone number:** +34 956 045 939 (Only available during office hours; Monday-Friday; 08:00-18:00)

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

- Acute Tox. 4 : Harmful in contact with skin.
- Carc. 2 : Suspected of causing cancer.
- Eye Dam. 1 : Causes serious eye damage.
- Flam. Liq. 3 : Flammable liquid and vapour.
- STOT SE 3 : May cause drowsiness or dizziness.
- Skin Irrit. 2 : Causes skin irritation.
- Skin Sens. 1 : May cause an allergic skin reaction.

#### 2.2 Label elements.

##### Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

**Danger**

H statements:

- |      |                                      |
|------|--------------------------------------|
| H226 | Flammable liquid and vapour.         |
| H312 | Harmful in contact with skin.        |
| H315 | Causes skin irritation.              |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage.           |
| H336 | May cause drowsiness or dizziness.   |
| H351 | Suspected of causing cancer.         |

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ST-55-DISOLVENTE ST-55 RAPIDO FINTECH



Version: 1

Revision date: 29/11/2018

Page 2 of 13

Print date: 29/11/2018

### P statements:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor/...  
P321 Specific treatment (see ... on this label).  
P370+P378 In case of fire: Use... to extinguish.

### Contains:

2-methylpropan-1-ol,iso-butanol  
n-butyl acetate  
2-butanone oxime,ethyl methyl ketone oxime,ethyl methyl ketoxime

### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not Applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 616-014-00-0 CAS No: 96-29-7 EC No: 202-496-6 Registration No: 01-2119539477-28-XXXX	2-butanone oxime,ethyl methyl ketone oxime,ethyl methyl ketoxime	55 - 100 %	Acute Tox. 4 *, H312 - Carc. 2, H351 - Eye Dam. 1, H318 - Skin Sens. 1, H317	-
Index No: 607-025-00-1 CAS No: 123-86-4 EC No: 204-658-1 Registration No: 01-2119485493-29-XXXX	[1] n-butyl acetate	10 - 20 %	Flam. Liq. 3, H226 - STOT SE 3, H336	-
Index No: 603-108-00-1 CAS No: 78-83-1 EC No: 201-148-0 Registration No: 01-2119484609-23-XXXX	[1] 2-methylpropan-1-ol,iso-butanol	10 - 20 %	Eye Dam. 1, H318 - Flam. Liq. 3, H226 - STOT SE 3, H335 - STOT SE 3, H336 - Skin Irrit. 2, H315	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

\* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

## SECTION 4: FIRST AID MEASURES.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ST-55-DISOLVENTE ST-55 RAPIDO FINTECH



**Version: 1**

**Revision date: 29/11/2018**

**Page 3 of 13**

**Print date: 29/11/2018**

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

#### **4.1 Description of first aid measures.**

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### **Inhalation.**

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

#### **Eye contact.**

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

#### **Skin contact.**

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners. The use of personal protective equipment is recommended for people providing first aid (see section 8).

#### **Ingestion.**

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### **4.2 Most important symptoms and effects, both acute and delayed.**

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

Long-term chronic exposure may result in injury to certain organs or tissues.

Contact with eyes may cause irreversible damage.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

#### **4.3 Indication of any immediate medical attention and special treatment needed.**

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

### **SECTION 5: FIREFIGHTING MEASURES.**

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

#### **5.1 Extinguishing media.**

##### **Suitable extinguishing media:**

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

##### **Unsuitable extinguishing media:**

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

#### **5.2 Special hazards arising from the mixture.**

##### **Special risks.**

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

#### **5.3 Advice for firefighters.**

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ST-55-DISOLVENTE ST-55 RAPIDO FINTECH



Version: 1

Revision date: 29/11/2018

Page 4 of 13

Print date: 29/11/2018

### **Fire protection equipment.**

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

### **6.1 Personal precautions, protective equipment and emergency procedures.**

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

### **6.2 Environmental precautions.**

Prevent the contamination of drains, surface or subterranean waters, and the ground.

### **6.3 Methods and material for containment and cleaning up.**

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

### **6.4 Reference to other sections.**

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

## **SECTION 7: HANDLING AND STORAGE.**

### **7.1 Precautions for safe handling.**

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

### **7.2 Conditions for safe storage, including any incompatibilities.**

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

### **7.3 Specific end use(s).**

Not available.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.**

### **8.1 Control parameters.**

Work exposure limit for:

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## ST-55-DISOLVENTE ST-55 RAPIDO FINTECH

Version: 1  
Revision date: 29/11/2018

Page 5 of 13  
Print date: 29/11/2018

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
n-butyl acetate	123-86-4	United Kingdom [1]	<b>Eight hours</b>	150	724
			<b>Short term</b>	200	966
		United States [2] (Cal/OSHA)	<b>Eight hours</b>	150	
			<b>Short term</b>	200	
		United States [3] (NIOSH)	<b>Eight hours</b>	150	
			<b>Short term</b>	200	
		United States [4] (OSHA)	<b>Eight hours</b>	150	710
			<b>Short term</b>		
2-methylpropan-1-ol,iso-butanol	78-83-1	United Kingdom [1]	<b>Eight hours</b>	50	154
			<b>Short term</b>	75	231
		United States [2] (Cal/OSHA)	<b>Eight hours</b>	50	
			<b>Short term</b>		
		United States [3] (NIOSH)	<b>Eight hours</b>	50	
			<b>Short term</b>		
		United States [4] (OSHA)	<b>Eight hours</b>	100	300
			<b>Short term</b>		

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[2] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[3] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[4] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
2-butanone oxime,ethyl methyl ketone oxime,ethyl methyl ketoxime CAS No: 96-29-7 EC No: 202-496-6	DNEL (Workers)	Inhalation, Long-term, Local effects	3,33 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	9 (mg/m <sup>3</sup> )
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	DNEL (Workers)	Inhalation, Long-term, Systemic effects	480 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	102,34 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Systemic effects	960 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Systemic effects	859,7 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Long-term, Local effects	480 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Local effects	102,34 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Local effects	960 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Local effects	859,7 (mg/m <sup>3</sup> )
	DNEL (General population)	Oral, Long-term, Systemic effects	3,4 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	3,4 (mg/kg bw/day)
	2-methylpropan-1-ol,iso-butanol CAS No: 78-83-1 EC No: 201-148-0	DNEL (Workers)	Inhalation, Long-term, Local effects
DNEL (General population)		Inhalation, Long-term, Local effects	55 (mg/m <sup>3</sup> )

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ST-55-DISOLVENTE ST-55 RAPIDO FINTECH



Version: 1

Revision date: 29/11/2018

Page 6 of 13

Print date: 29/11/2018

Name	Details	Value
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	aqua (freshwater)	0,18 (mg/l)
	aqua (marine water)	0,018 (mg/l)
	aqua (intermittent releases)	0,36 (mg/l)
	PNEC STP	35,6 (mg/l)
	sediment (freshwater)	0,981 (mg/kg sediment dw)
	sediment (marine water)	0,0981 (mg/kg sediment dw)
2-methylpropan-1-ol,iso-butanol CAS No: 78-83-1 EC No: 201-148-0	aqua (freshwater)	0,4 (mg/L)
	aqua (marine water)	0,04 (mg/L)
	aqua (intermittent releases)	11 (mg/L)
	STP	10 (mg/L)
	sediment (freshwater)	1,52 (mg/kg sediment dw)
	sediment (marine water)	0,152 (mg/kg sediment dw)
	soil	0,0699 (mg/kg soil dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

<b>Concentration:</b>	<b>100 %</b>		
<b>Uses:</b>	<b>Dilution and cleaning of solvent base products Custom Creative</b>		
<b>Breathing protection:</b>			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
<b>Hand protection:</b>			
PPE:	Protective gloves against chemicals.		
Characteristics:	«CE» marking, category III.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.): > 480	Material thickness (mm): 0,35
<b>Eye protection:</b>			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against splashing liquid, dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ST-55-DISOLVENTE ST-55 RAPIDO FINTECH





Version: 1

Revision date: 29/11/2018

Page 7 of 13

Print date: 29/11/2018

Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.	
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	
<b>Skin protection:</b>		
PPE:	Anti-static protective clothing.	
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.	
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5	
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.	
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.	
PPE:	Anti-static safety footwear.	
Characteristics:	«CE» marking, category II.	
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346	
Maintenance:	The footwear should be checked regularly	
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.	

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

#### 9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour  
Colour: N.A./N.A.  
Odour: N.A./N.A.  
Odour threshold: N.A./N.A.  
pH: N.A./N.A.  
Melting point: N.A./N.A.  
Boiling Point: 155 °C  
Flash point: 40 °C  
Evaporation rate: N.A./N.A.  
Inflammability (solid, gas): N.A./N.A.  
Lower Explosive Limit: N.A./N.A.  
Upper Explosive Limit: N.A./N.A.  
Vapour pressure: 3,312  
Vapour density: N.A./N.A.  
Relative density: 0,899  
Solubility: N.A./N.A.  
Liposolubility: N.A./N.A.  
Hydrosolubility: N.A./N.A.  
Partition coefficient (n-octanol/water): N.A./N.A.  
Auto-ignition temperature: N.A./N.A.  
Decomposition temperature: N.A./N.A.  
Viscosity: N.A./N.A.  
Explosive properties: N.A./N.A.  
Oxidizing properties: N.A./N.A.  
N.A./N.A.= Not Available/Not Applicable due to the nature of the product

#### 9.2 Other information.

Dropping point: N.A./N.A.  
Blink: N.A./N.A.  
Kinematic viscosity: N.A./N.A.  
N.A./N.A.= Not Available/Not Applicable due to the nature of the product

### SECTION 10: STABILITY AND REACTIVITY.

-Continued on next page.-



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ST-55-DISOLVENTE ST-55 RAPIDO FINTECH



Version: 1

Revision date: 29/11/2018

Page 8 of 13

Print date: 29/11/2018

### 10.1 Reactivity.

If the storage conditions are satisfied, does not produce dangerous reactions.

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

### 10.4 Conditions to avoid.

Avoid the following conditions:

- High temperature.
- Static discharge.
- Contact with incompatible materials.
- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

### 10.5 Incompatible materials.

Avoid the following materials:

- Explosives materials.
- Toxic materials.
- Oxidizing materials.

### 10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

## SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT PREPARATION. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

### Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
n-butyl acetate	Oral	LD50	Rat	10800 mg/kg bw [1]
		[1] Acute Toxicity Data. Journal of the American College of Toxicology, Part B. Vol. 1, Pg. 196, 1992		
CAS No: 123-86-4      EC No: 204-658-1	Dermal	LD50	Rabbit	>17600 mg/kg bw [1]
		[1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 7, 1974		
	Inhalation	LC50	Rat	1.85 mg/l/4 h [1]
		[1] Inhalation Toxicology. Vol. 9, Pg. 623, 1997		
2-methylpropan-1-ol,iso-butanol	Oral	LD50	Rat	2830 mg/kg bw [1]
		[1] Christopher, S.M. November 30, 1993. "Isobutanol: Acute toxicity and irritancy testing using the rat (peroral and inhalation toxicity) and the rabbit (cutaneous and ocular tests)". Bushy Run Research Center, Union Carbide Corp. Lab. Proj. ID 92U1166		

-Continued on next page.-



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ST-55-DISOLVENTE ST-55 RAPIDO FINTECH



Version: 1

Revision date: 29/11/2018

Page 9 of 13

Print date: 29/11/2018

CAS No: 78-83-1      EC No: 201-148-0	Dermal	LD50      Rabbit      4240 mg/kg bw [1] [1] Smyth H.F. Jr. et al.: AMA Arch. Ind. Hyg. Occup. Med., 10, 61-68, (1954) as cited in IUCLID.
	Inhalation	

a) acute toxicity;

Product classified:

Acute toxicity (Dermal), Category 4: Harmful in contact with skin.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 1.467 mg/kg

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitizer, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Product classified:

Carcinogen, Category 2: Suspected of causing cancer.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
n-butyl acetate	Fish	LC50	Fish	81 mg/l (96 h) [1]

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ST-55-DISOLVENTE ST-55 RAPIDO FINTECH



Version: 1

Revision date: 29/11/2018

Page 10 of 13

Print date: 29/11/2018

CAS No: 123-86-4      EC No: 204-658-1		[1] Wellens, H. 1982. Comparison of the Sensitivity of Brachydanio rerio and Leuciscus idus by Testing the Fish Toxicity of Chemicals and Wastewaters. Z.Wasser-Abwasser-Forsch. 51(2):49-52 (GER) (ENG ABS). Dawson, G.W., A.L. Jennings, D. Drozdowski, and E. Rider 1977. The Acute Toxicity of 47 Industrial Chemicals to Fresh and Saltwater Fishes. J.Hazard.Mater. 1(4):303-318 (OECDG Data File)
	Aquatic invertebrates	EC50      Daphnia sp.      44 mg/l (48 h) [1] [1] publication, 1959
CAS No: 78-83-1      EC No: 201-148-0	Aquatic plants	EC50      Desmodesmus subspicatus (reported as Scenedesmus subspicatus)      674.7 mg/l (72 h) [1] [1] Method: other: algae growth inhibition test, according to Umweltbundesamt (German Federal Environment Agency) (proposal/draft, version February 1984)
	Fish	EC50      Pimephales promelas      1430 mg/L (96 h h) [1] [1] Brooke, L.T. et al., 1984. Acute Toxicities of Organic Chemicals to Fathead Minnows (Pimephales promelas). Vol. I. Center for Lake Superior Environmental Studies. University of Wisconsin-Superior.
CAS No: 78-83-1      EC No: 201-148-0	Aquatic invertebrates	EC50      Daphnia magna      1300 mg/L (48 h) [1] [1] Elnabarawy MT, Welter AN, Robideau RR. 1986. relative sensitivity of three daphnid species to selected organic and inorganic chemicals. Environ Toxicol Chem 5: 393-398.
	Aquatic plants	EC90      Selenastrum capricornutum (Pseudokirchnerella subcapitata)      717 mg/L (96 h) [1] [1] Wong, D.C.L, P.B. Dorn, and J.P. Salanitro. 1998. Aquatic Toxicity of Four Oxy-Solvents. Equilon Enterprises, LLC Technical Information Record WTC-3520.

### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
n-butyl acetate CAS No: 123-86-4      EC No: 204-658-1	1,78	-	-	Very low
2-methylpropan-1-ol, iso-butanol	0,76	-	-	Very low

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ST-55-DISOLVENTE ST-55 RAPIDO FINTECH



**Version: 1**

**Revision date: 29/11/2018**

**Page 11 of 13**

**Print date: 29/11/2018**

CAS No: 78-83-1	EC No: 201-148-0				
-----------------	------------------	--	--	--	--

### 12.4 Mobility in soil.

No information is available about the mobility in soil.  
The product must not be allowed to go into sewers or waterways.  
Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

## SECTION 13 DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.  
Follow the provisions of Directive 2008/98/EC regarding waste management.

## SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

### 14.1 UN number.

UN No: UN1263

### 14.2 UN proper shipping name.

Description:

ADR: UN 1263, PAINT RELATED MATERIAL, 3, PG III, (D/E)

IMDG: UN 1263, PAINT RELATED MATERIAL, 3, PG III

ICAO/IATA: UN 1263, PAINT RELATED MATERIAL, 3, PG III

### 14.3 Transport hazard class(es).

Class(es): 3

### 14.4 Packing group.

Packing group: III

### 14.5 Environmental hazards.

Marine pollutant: No

### 14.6 Special precautions for user.

Labels: 3

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ST-55-DISOLVENTE ST-55 RAPIDO FINTECH



Version: 1  
Revision date: 29/11/2018

Page 12 of 13  
Print date: 29/11/2018



Hazard number: 30  
ADR LQ: 5 L  
IMDG LQ: 5 L  
ICAO LQ: 10 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.  
Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E  
Proceed in accordance with point 6.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

## SECTION 15: REGULATORY INFORMATION.

### 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

#### Volatile organic compound (VOC)

VOC content (p/p): 100 %  
VOC content: 898,517 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant for the water (Germany): WGK 1: Slightly hazardous for the water. (Autoclassified according to the AwSV Regulations)

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ST-55-DISOLVENTE ST-55 RAPIDO FINTECH



**Version: 1**

**Revision date: 29/11/2018**

**Page 13 of 13**

**Print date: 29/11/2018**

Carc. 2 : Carcinogen, Category 2  
Eye Dam. 1 : Serious eye damage, Category 1  
Flam. Liq. 3 : Flammable liquid, Category 3  
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3  
Skin Irrit. 2 : Skin irritant, Category 2  
Skin Sens. 1 : Skin sensitiser, Category 1

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

#### Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
AwSV: Facility Regulations for handling substances that are hazardous for the water.  
BCF: Bioconcentration factor.  
CEN: European Committee for Standardization.  
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.  
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.  
EC50: Half maximal effective concentration.  
PPE: Personal protection equipment.  
IATA: International Air Transport Association.  
ICAO: International Civil Aviation Organization.  
IMDG: International Maritime Code for Dangerous Goods.  
LC50: Lethal concentration, 50%.  
LD50: Lethal dose, 50%.  
Log Pow: Logarithm of the partition octanol-water.  
NOEC: No observed effect concentration.  
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.  
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.  
WGK: Water hazard classes.

#### Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.